
PRODUCT FACT SHEET

3701
General-Purpose
Duct Tape

PRODUCT

General-Purpose Duct Tape

DESCRIPTION

Backing: Polyethylene Coated Cloth
Total Thickness: 9 mils
Adhesive: Natural Rubber
Color: Silver

PHYSICAL PROPERTIES

Tensile Strength (lbs. / in.)	28.8	ASTM D 1000
Adhesion to Steel (oz. / in.)	55	* PSTC-1

MAXIMUM PERFORMANCE TEMPERATURE

200° F

TYPICAL APPLICATIONS

- > Temporary holding and bonding
 - > Bundling, Patching, Splicing, Mending, and Temporary Repairs
 - > Closing and reinforcing packages
-

NOTES:

The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine their suitability before adapting them on a commercial scale.

*Pressure Sensitive Tape Council



100 South Puente Street | Brea, CA 92821
Phone (714) 255-7888 | Toll Free Phone (800) 258-8273
Fax (714) 990-5671 | Toll Free Fax (800) 235-8273
www.sta-tape.com