

PRODUCT

130 lb. Tensile Strength Glass Reinforced Filament Tape**DESCRIPTION**

Backing:	1.0 mil Oriented Polypropylene/Fiberglass
Thickness:	5.2 mil
Adhesive:	Rubber
Color:	White

PHYSICAL PROPERTIES

Tensile Strength (lbs/in)	130 minimum	* PSTC-31
Elongation (% at break)	4 maximum	PSTC-31
Adhesion (oz/in)	76	PSTC-1

APPLICATION TEMPERATURE **

32° F to 150° F

OPERATING TEMPERATURE ***

0° F to 176° F Nominal

TYPICAL APPLICATIONS

For packing, bundling and splicing.

NOTES:

All properties are approximate and based on the average of a series of manufacturer tests. These tests are conducted in accordance with industry recommended and accepted test methods. A particular roll may vary from these averages. The values do not represent a guarantee by the manufacturer and it is recommended that each tape be evaluated by the user under actual end-use conditions prior to approval and purchase. Seller terms and conditions of sale apply to all purchases.

PSTC: Pressure Sensitive Tape Council*** Application Conditions:** The conditions at which the tape is being unwound and applied to the substrate. Under the specified application conditions, the tape should unwind to the substrate properly and perform as normally expected.******* The tape is exposed to the operating conditions for 1 year. Under the specified operating conditions, the tape should adhere to the substrate properly and perform as normally expected.

SPE182

**SEKISUI TA INDUSTRIES, INC.****100 SOUTH PUENTE STREET • BREA, CA 92821****(800) 258-8273 / (714) 255-7888 PHONE • (800) 235-8273 FAX**